

Implementing and Maintaining Best Management Practices

Jonathan Koepke, CPESC, LEED-AP
Vice President, General Manager




Overview

- Understanding the Basics
 - Erosion Control Vs. Sediment Control
 - BMP Selection
 - Proper Installation
- Sediment Control BMPs
- Erosion Control BMPs
- Strategies for Problem Solving

The Basics

- To understand how we impact and are impacted by water, the concept of the water cycle is key



Graphics credit:
Delaware Dept. of
Natural Resources

Consistent Terminology – Erosion Vs. Sedimentation

- Soil **erosion** is the process by which soil particles become detached by water, wind, or gravity and are transported from their original location.




Consistent Terminology – Erosion Vs. Sedimentation

- Sedimentation is the deposition of the eroded material



Understanding Types of Erosion Impacts BMP Selection

1. Raindrop erosion
2. Sheet erosion
3. Rill and gully erosion
4. Streambank and bed erosion
5. Wind erosion



Graphics credit IL Urban Manual

BMP Selection - What can this site teach us?

- Incorrectly applied erosion control can actually increase erosion
- For example: Silt fence should not be installed up and down slope
- Fiber rolls may have been used to break-up slope length



BMP Selection - Planning and Phasing



- Many erosion and sediment control practices are temporary, and are designed to be installed at different periods of the construction activity.
- Practices should be installed as they become appropriate and should not be delayed so that all measures can be installed at the same time.

BMP Implementation - Installation of Practices

- Ensure that you have a knowledgeable and reliable contractor installing erosion and sediment control measures
- Make sure that contractors are using products appropriately



The Two Most Important BMPs

- **Proper Communication and Coordination**

- ✓ Engineer, Contractors, Sub-Contractors, Land Development, House Line, Utility Employees, Regulators, and Permitting Agencies must all understand SESC objectives

- **Proper Installation and Maintenance**

- ✓ Structural, mechanical, vegetative, and chemical SESC measures must be properly installed/applied and maintained in order to be effective and comply with permits



Sediment Control BMPs

Sediment Control BMPs

Intended to capture sediments and remove them from suspension

- Function best in cooperation with erosion control practices
- High maintenance
- Very temporary



Sediment Control BMPs

MAINTENANCE

Rule of Thumb –

Perform maintenance when sediment holding capacity is $\frac{1}{3}$ to $\frac{1}{2}$ full

MOST SITES –

Every significant rainfall event



Sediment Control BMPs

- Silt fences
- Ditch checks
- Polymer Enhanced BMPs
- Street and curb protection
- Storm sewer inlet protection
- Concrete washout
- Sediment traps/basins
- Skimmers / Outlet Risers
- Dewatering / Pump Discharge Filtration
- Polyacrylamides

Silt Fence

Installation

- Trenched into ground, backfilled and compacted, or static sliced and compacted
- 6 Inch (15.25cm)
- Stake Spacing—5 Feet (1.5m)
- Wire Backing (if required)



What do you mean there is a problem with my silt fence?



Silt Fence

Installation

- Static Slicing Method
- Preferred method by EPA and ASCE



Silt Fence




Maintenance

- Repair compromised areas
- Remove accumulated silt
- Ensure fence is properly intercepting all drainage routes

Ditch Checks

Installation


- Intercept flow of entire ditch or swale
- Direct contact with soil
- Spacing
- Center lower than sides



Ditch Check Spacing Guidelines

- Ditch checks should be spaced in a manner that runoff discharges from “pool to pool”

This slows water velocity down and gives more time for water to infiltrate into the ground and causes sediment to fall out of suspension!



Ditch Checks

Installation

- Geometry



Ditch Checks

Installation

- Geometry



Ditch Checks

Maintenance

- Replace or repair failed checks
- Repair rills and gullies
- Remove accumulated silt
- DO NOT USE STRAW BALES



Ditch Checks

Use Alternative Measures to Straw Bales



Ditch Checks

??????



Ditch Checks

Use Alternative Measures to Straw Bales


Don't just count
on a better
product solving
the problem!

Make sure
sized
appropriately
and it is
installed
properly!



Ditch Checks

Geotextile Encased Urethane Foam – Silt Dike




Ditch Checks

Polyethelene Ridges –
Allow V egetation to Establish Underneath



Fiber Log (Sediment Log) Ditch Checks



Polymer Enhanced Ditch Check



Polymer Enhanced Ditch Check



Polymer Enhanced BMPs

- Initial Installation of PAM on Rock Check Dam
- Additional grading of the ditchline actively taking place



Polymer Enhanced BMPs (PEBMPs)

- Temporary Seeding in ditchline
- Reactivation of Ditch Check
- Note Water Clarity Downstream of PAM Enhanced Ditch Check
- New Jute "Layered" on Top – Cleanout accumulated sediment above check dam



Streets and Curb Inlets

Primary Goal is to Prevent Sediment from Entering the Roadways



Streets and Curb Inlets

Primary Goal is to Prevent Sediment from Entering the Roadways



- Provide silt fence or barriers at curb cuts
- Prohibit the use of soil for ramping curbs
- Overexcavate area behind curb until final grade can be established

Streets and Curb Inlets

- Ensure entire curb inlet is protected
- Replace or repair inlet protection as necessary
- Inspect streets and gutters daily and clean and scrape at least weekly



Streets and Curb Inlets

Primary Goal is to Prevent Sediment from Entering the Roadways



Storm Sewer Inlets – Area Drains



Explore all
alternative measures

Use all the tools in the
toolbox



Storm Sewer Inlets – Curb Side



Explore all
alternative measures



Storm Sewer Inlets – Curb Side



Good

Bad and Ugly



Streets and Curb Inlets

Primary Goal is to Prevent Sediment from Entering the Roadways



Streets and Tracking

- Once sediment enters roadways then it becomes increasingly difficult to control.
- Sedimentation Issues
- Safety Issues



Concrete Washout Areas

- Designated areas to store, pool, filter, and allow easy removal of concrete wash



GOOD!!



BAD!!

Concrete Washout Areas

- Designated areas to store, pool, filter, and allow easy removal of concrete wash



Silt Curtain or Turbidity Curtain

- Temporary floating "silt fence"
- Designed to be installed in-line with flow NOT across flow
- Used when working on streambanks



Silt Curtain or Turbidity Curtain

- Should be anchored at upstream and downstream end
- “Hooked into bank at limits of disturbance
- Anchor posts in flow line to “guide” fence and prevent it from “flapping” in current



Sediment Traps / Basins

- Traps designed for 5 acre (2 Ha) or less drainage area;
Basins designed for 5+ acre (2 Ha) drainage areas



Sediment Traps / Basins

- Minimum Sediment Trap/Basin Storage Requirements (per USEPA requirements):
 - Composed of equal volumes of wet (below permeable fill) and dry detention storage
 - Must be sized to accommodate sediment storage for the expected soil loss over the course of the project (minimum of 1 Year)
 - Sized for the runoff from greater of:
 - **2-year, 24-hour** storm event during maximum runoff conditions
 - **134 yd³/acre (253 m³/Hectare)** of drainage area

Sediment Basin/Trap Outlet Protection



Culvert Inlet Protection – Keeps Sediment in Trap or Basin

Temporary Perforated Stand Pipes



Make sure they are properly anchored

Skimmers

- Typically PVC
- Linked into manhole
- Temporarily bypass outlet pipe
- Float or fixed
- Draw off of the top of the water column
- Remove before winter



Skimmers



Dewatering Activities

- Intake floated or placed in Sump Pit



Dewatering Activities

- Intake floated or placed in Sump Pit

Sump
Pit



Dewatering Activities

- Outlet onto impervious, energy-dissipating surface
- Filter placed on outlet
- Dewatering to Sediment Basins or silt traps – NOT DIRECTLY TO STREAM or STORMWATER FACILITIES



Filter Bags

- Geotextile fabric bag
- Traps large particles
- Place on stabilized ground
- Use pretreatment measures
- Monitor, monitor, monitor



Dewatering Activities

- Dewatering to Sediment Basins or silt traps – NOT DIRECTLY TO STREAMS or STORMWATER FACILITIES



Polyacrylamides (PAM)

- Cationic – Positively Charged
- Anionic – Negatively Charged
- Anionic PAMs have not been proven to be toxic to aquatic, soil, or plant species when used as directed
- Cationic PAMs on the other hand are toxic to fish and must not be used for surface water applications
- Any polymer used should have all MSDS information available and documentation of acute and chronic toxicity for appropriate aquatic vertebrates or invertebrates (Work with Local, Provincial, & National Regulatory Bodies)

Polyacrylamide (PAM)

- Forms: dry powder, solution, emulsion, logs




PAM Use for Sediment Control

- Clarification of turbid discharge water
 - Active introduction of PAM
 - Mixing of PAM and Discharge Water
 - Capture of Flocculants
- Polymer must be selected based on site specific soils testing, or tested on site specific soils
- Adequate time must be given for PAM to reach adequate concentration to create flocculation


Flocculation by PAM

- PAM binds (or flocculates) suspended sediment by attaching to several soil particles forming a larger aggregate or floc.



Flocculation by PAM

- The larger (and now heavier) flocs then settle out of suspension.



Flocculation



Polymer Dewatering Swale Treatment



Polymer Dewatering Swale Treatment



Polymer Dewatering Swale Treatment





Erosion Control Best Management Practices

Prevent Storm Water Contact With Bare Soil

- Storm water from the sky – Rainfall
- Storm Water from adjacent areas - Run-on



Methods of Erosion Control

- Limited Disturbance
- Vegetative Practices
- Mulching / Erosion Control Blanket
- Run-On / Runoff Control

Limited Grading Where Possible

- Limit the amount and duration that areas are exposed to rainfall impact, run-on, run-off, and wind



Vegetative Stabilization Practices

Permanent Seeding

Temporary Seeding



Sodding Plugging



Long Term Erosion Control

- The most effective and efficient means of controlling soil erosion on construction sites is a healthy and full stand of vegetation.



That's great, but how do we get there?

Vegetative Stabilization

- Typical construction sites provide challenges to stabilizing soils
- Vegetation establishment is difficult at best
 - Low nutrient content
 - Little natural soil structure
 - Clay soils are prone to sealing off
 - High soil compaction
 - Little moisture retention
 - Low temperature moderation



Seeding

- Keys to Success

- Ground Preparation
- Proper Seed Selection
- Soil Amendments
- Proper Installation



No matter what, seeding on poor soils takes additional time to mature.

Methods of Seeding

- Broadcast



Methods of Seeding

- Mechanical



Methods of Seeding

- Hydroseeding



Temporary Seeding

- Seed Mixes

- Annuals

- Seed Oats – Hearty, Fast Germinating & Growing, Frost Intolerant, Good in Spring
 - Annual Rye – Fast Germinating & Growing, Will Reseed, Great quick cover all year, slightly more frost tolerant
 - Cereal Rye / Winter Wheat – Great in Fall, Germinates in colder temps, winter survivorship

- Perennials

- Perennial Rye – Durable, Fast Germinating, Dense
 - Timothy – Pasture Grass, Very fine Seed, Durable
 - Creeping Red Fescue – Simple durable and fast growing
 - Tall Fescue – Good cover, grows dense and tolerates drought
 - Alsike Clover – Not always desirable (especially in native areas) but fast growing, spreads in, tolerant of both drought & wetness,

Seeding Practices

- Key to Successful Seeding on Construction Sites
 - Each site is different
 - Choose seed mixes that are appropriate for the soil conditions
 - Proper Installation is KEY!!
 - Soil Amendments
 - Mulching

Mulching / Terraseeding / Erosion Control Blanket

- The job of any mulching is to stabilize soils and provide ideal growing conditions for seeding.
 - Erosion Control
 - Moisture Retention
 - Temperature Moderation
 - Nutrients and Organic Material



Erosion Control Blanket

Practice & Product Selection Criteria

- Slope Steepness & Length
- Functional Longevity
- Velocities & Sheer Stresses
- Staple Pattern
- Soil Conditions



Erosion Blanket / TRM Installation



Erosion Control Blanket

Installation

- Soil surface stable and free of rocks and obstructions
- Material meets specifications
- Protected from contributing disturbed areas
- Direct contact with soil



Erosion Control Blanket



INSTALLATION

- Anchored on summit of slope
- Unrolled parallel to primary direction of flow
- Overlapped in the direction of flow
- Staple Pattern & Quantity is Correct

Erosion Control Blanket

INSTALLATION



- Staple Pattern & Quantity is Correct

Mulching

Practice & Product Selection Criteria

- Slope
- Soil Conditions
- Duration Needed
- Access
- Cost

Options for Mulching

- Straw Mulching
- Hydromulching
- Compost Mulching
(Terraseeding)

Straw Mulching

- Economical
- Application Rate of 2 Tons per Acre minimum
- Crimping necessary



Straw Mulching!!!!



Straw Crimping



Hydromulching

Considerations

- Slope
- Access
- Duration
- Types of Fiber
- Bonding Agent / Tackifier
- Seeding with mulching?
- Mix Ratio
- Rate of Application



Hydromulching

INSTALLATION



- Mix Thoroughly
- Add water first, then lightest to heaviest elements
- Spray from two opposing directions
- Ensure appropriate application rate

Compost Mulching

- What is Compost Mulching?
- A layer of loosely applied compost or composted material that is placed on the soil in disturbed areas to control erosion and retain sediment resulting from sheet-flow runoff.¹



¹ USEPA – NPDES Stormwater Menu of BMPs

Terra Seeding

- Application of Compost –
 - ½ inch thick with seed - November 5



Terraseeding

- Application of Compost – ½ inch thick with seed



March 18 - Rainfall



May 7 - Rainfall

Runoff Control Measures

Protect Disturbed Soil Areas From Erosion

- BMPs to protect from erosion
 - Top of slope dikes
 - Slope drains
 - Gravel bag berms or fiber rolls



Diversions

- BMPs practicable to protect disturbed areas from run-on are:
- Earth dikes/drainage swales and lined ditches
- Sandbag Barriers



Other BMPs

- Spill Prevention and Clean-Up
- Waste Disposal
 - Dumpsters
 - Porta-potties
- Secondary Containment of Pollutants
- Street sweeper
- Dust control
- Material Storage



Strategies for Problem Solving with BMPs

- Identify the cause of the problem, not the symptom
- Select the appropriate BMP for the type of problem you are encountering
- Identify how long you need the solution to last
- Be creative and mix your BMPs
- There is no magic carpet or silver bullet

Problem Solving

Are Different Practices Needed?



Problem Solving

More is not better



Problem Solving


- Develop Treatment Train



Why BMPs Matter



Use Your BMPs Wisely



Questions?



Practical Land Improvement Solutions for Over 35 Years

Jonathan Koepke, CPESC, LEED-AP
Vice President, General Manager
ENCAP, Inc.

1709 Afton Road, Sycamore, IL 60178
815-899-1621

www.encapinc.net
jkoepke@encapinc.net